



# TSW2R Multi-Master

## Graffiti, Paint and Marker Remover for Most Surfaces

### Product Data Sheet

**DEVELOPED TO REMOVE:** Oil and Latex Paints, Permanent Marker, Pen, Inks, Lipstick and Correction Fluid and More!

**FROM:** Most surfaces including TSW4 & TSW8 Acryli-Master Graffiti Resistant Coatings.

***Always test, rinse, and dry a small inconspicuous area for compatibility first!***

#### NOTE

For large areas, clean in sections. Not doing so could result in product evaporation prior to completing removal process. Avoid use in direct sunlight or when surfaces are warm to the touch. Product effectiveness is limited at temperatures below 45° and above 95° Fahrenheit. Use as supplied. Never dilute with any other liquids.

#### REMOVING MARKER

Apply remover on clean white cloth, rag or sponge then wipe defaced area. Suspended dyes and pigments must be soaked up, not doing so could result in staining surrounding area. Repeat until graffiti is gone, neutralize with TSW7™ or water. Light scrubbing may be necessary.

#### REMOVING SPRAY PAINT

Spray remover directly on defacement. Hold a clean white rag underneath to prevent from running down the wall. Allow enough time for TSW2R™ to react. This may take a few seconds to a few minutes depending on the thickness of the defacement. Agitate with cloth or sponge, then neutralize with TSW7™ or water.

Thicker layers of defacement may require use of a scrub brush. Repeat applications may be necessary. Removal from unpainted porous surfaces typically requires use of a pressure washer and a combination of TSW3G Mason-Master™ and TSW2R Multi-Master for improved results. If TSW2R™ is too aggressive for your surface, try TSW9 Plasti-Master™.

**HEALTH AND SAFETY INFORMATION** – KEEP OUT OF REACH OF CHILDREN. Use with adequate ventilation. Wear chemical resistant gloves and eye protection. Avoid skin contact as TSW2R™ can cause irritation to skin and eyes. **FIRST AID:** For skin contact, wash with soap and water. In case of eye contact flush with large amounts of water. If swallowed, DO NOT INDUCE VOMITING. If irritation persists, seek medical attention.

**Packaging:** TSW2R Multi-Master™ is packaged in 8oz spray, 24oz spray, one gallon and five gallon containers.

For complete safety information refer to SDS or call customer support at 800.447.2334.

**CHEM-TEL 24-Hour Emergency Contact # 800.255.3924**

Visit our website [www.TSWUSA.com](http://www.TSWUSA.com)

Questions? Comments? Contact tech support at 800.4GRAFFITI (800.447.2334)