



PRODUCT DATA SHEET

TSW3G Mason-Master™

Remover for Unpainted Porous Surfaces

DEVELOPED TO REMOVE: Spray paint, oil and latex paints and other common graffiti vandalism and overspray!

FROM: Concrete, Brick, Stone and most other unpainted porous surfaces.

****READ HEALTH AND SAFETY INFORMATION PRIOR TO USE****

DIRECTIONS: Always test, rinse, and dry a small inconspicuous area for compatibility first! Wear protective gear as noted in HEALTH AND SAFETY.

1. Spray directly on surface
2. Allow product to dwell for 15 - 30 minutes.
3. When solvent action appears complete and graffiti is loosened, use a pressure washer to remove defacement. (Hot water improves results)

Note: For large areas, clean in sections. Not doing so could result in product evaporation prior to removal or pressure washing. Begin removal by working from the bottom up as opposed to the top down. TSW3G may be applied with a paint roller. Avoid use in direct sunlight or when surfaces are warm to the touch. Product effectiveness is limited at temperatures below 45° and above 95° Fahrenheit. Use as supplied. Never dilute with any other liquids. Water neutralizes TSW3G™ – Use on dry surfaces only.

Repeat applications may be necessary. A preliminary application of TSW2R Multi-Master™ may be required on some surfaces for improved results. When TSW3G Mason-Master™ is not sufficient, spray (or roll) affected area with TSW2 Multi-Master™ first, followed by a thorough saturation of TSW3G Mason-Master™.

HEALTH AND SAFETY INFORMATION – Caution: Corrosive Liquid – Extremely irritating to skin and destructive to eyes. KEEP OUT OF REACH OF CHILDREN. Contains a blend of alkali and solvents – Containing runoff is recommended and mandatory in certain jurisdictions. Avoid contact with skin and eyes as TSW3G™ is extremely irritating to skin and destructive to eyes. Use with adequate ventilation. Wear chemical resistant gloves and eye protection. Do not take internally. **FIRST AID:** In case of skin contact, flush with large amounts of water. In case of eye contact, flush with large amounts of water for at least 15 minutes and seek medical attention. If swallowed, DO NOT INDUCE VOMITING. Contact poison control center. There are no known chronic health effects caused by the use of this product.

Packaging: TSW3G Mason-Master™ is packaged in an 8oz spray bottle, 24oz. spray, one gallon and five-gallon containers.

For complete safety information refer to SDS or call customer support at 800.447.2334.

CHEM-TEL 24-Hour Emergency Contact # 800.255.3924

Visit our website www.tswusa.com

Questions? Comments? Contact tech support at 800.4GRAFFITI (800.447.2334)