



PRODUCT DATA SHEET

TSW5 Spray Clean™

Internal Spray Rig Flush and Cleaner for Paint Brushes, Rollers and Equipment

DEVELOPED AT THE REQUEST OF PAINT PROFESSIONALS TO REMOVE WET OR DRIED PAINT FROM BRUSHES, ROLLERS AND SPRAY EQUIPMENT PARTS. ALSO CAN BE USED AS A FLUSH TO INTERNALLY CLEAN AIRLESS SPRAYERS

INSTRUCTIONS FOR CLEANING BRUSHES, ROLLERS AND SPRAY EQUIPMENT PARTS: Add one-part TSW5 to four parts water. Soak until the paint has softened and loosened (generally 10-15 minutes). For dried, hardened paint soak a few hours to overnight. Use a pick to remove from areas that are thickly coated. Once paint has been removed, rinse thoroughly with water.

INSTRUCTIONS FOR INTERNAL CLEANING: For cleanup after each job, add 4oz. of TSW5 to 3 gallons of fresh water. As a final rinse, run the solution using the same procedure as when painting through the entire apparatus. The final few ounces of water should be clear. If paint residue is still in the water, repeat the process. **Do not store TSW5 in the apparatus.**

HEALTH AND SAFETY INFORMATION – KEEP OUT OF REACH OF CHILDREN. Use with adequate ventilation. Wear rubber gloves and guard against splashing into eyes. Product is irritating to skin and extremely irritating into eyes. **FIRST AID:** For skin contact, flush with large amounts of water. For eye contact, flush with water for fifteen minutes. If irritation persists, seek medical attention. There are no known chronic health problems associated with the use of this product.

Packaging: TSW5 Spray-Clean™ is packaged in 4oz., 24oz. one-gallon and five-gallon quantities.

For complete safety information refer to SDS or call customer support at 800.447.2334.

CHEM-TEL 24-Hour Emergency Contact # 800.255.3924

Visit our website www.tswusa.com

Questions? Comments? Contact tech support at 800.4GRAFFITI (800.447.2334)